## Mountfield

## SP465R

SKU: 299489038/M19

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>		
Product Name OescriptionSP465RProduct Name DescriptionRear Roller LawmowerHomologation nameNTL 484 TR-RPower SourceHordoPotoget SourceStoceEngine BrandIndodeEngine ModelSCNe 145 OHV AutochokeEngine ModelSCNe 145 OHV AutochokeRepower outputStoleStaterRecoilFuel Tank CapacityOS LCutting MethodStoleCutting MethodStole<	SKU	299489038/M19
Product Name DescriptionRear Roller LawmowerHomologation nameNTL 484 TR-RPower SourcePetrolCapacity145 ccEngine BrandIondaEngine ModelColvo: 145 OHV AutochokeRatpower output275 kW @ 2900 rpmStaterRecoilFuel Tank Capacity0.95 LCutting MethodCollectingCutting MethodCollectingCutting MethodScellCutting MethodScell	EAN	8008984817562
Honologation nameNTL 434 TR-RPower SourcePerolaPower SourcePerolaCapacity145 c3 C4	Product Name	SP465R
Power SourcePetrolCapacity145 ccCapacity146 dcEngine BrandCVXe 145 OHV AutochokeEngine Model275 kW @ 2900 rpnStaterRecoilFuel Tank Capacity0.95 LCutting widthCollectingCutting MethodCollectingDeck materialStelCutting MethodStelCutting height adjustmentStelCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledMaximum speed forwardStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledMaximum speed forwardStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledCutting height adjustmentStel/PropelledCuttin	Product Name Description	Rear Roller Lawnmower
CharacteriesStateCapacity145 ccEngine BrandHondaEngine ModelGCVxe 145 OHV AutochokeNet power output2.75 KW @2900 pmStaterRecoilFuel Tank Capacity0.95 LEngine oil tank capacity0.95 LCutting widthGCVce 145 OHV AutochokeDeck material0.95 LCutting height adjustmentGolectingCutting height positionsSo SolitonsCutting height ange0.97 0 mmTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGildraft angen capacity9Ausancted sound power level (LWA)-9Ausancted sound power level dB(A)945 x530 x480Pack dimensions (LxWxH)9.45 x50 x480Pack weight5.50 mmProduct length5.50 mmProduct length5.50 x480Product length5.50 x480Pack weight5.50 x480Pack weight5.50 x480Product length5.50 mmProduct length5.50	Homologation name	NTL 484 TR-R
FinanceHondaEngine BrandGCVxe 145 OHV AutochokeEngine ModelGCVxe 145 OHV AutochokeNet power output2.75 KW @2900 rpmStarterRecoilFuel Tank Capacity0.95 LEngine oil tank capacity0.4 LCutting width46 cmCutting MethodCollectingDeck materialSteelCutting height positionsSolfionsCutting height positionsSolf-propelledTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacityS5 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGigAnd9.6Ausanced sound power level (LWA)- Berarder art B(A)9.6Product meight9.6Product weight9.4 ksProduct length5.5 ksProduct weight9.6Starter discuttion forward bearings9.6Guaranteed sound power level (LWA)- Berarder art B(A)9.6Product length9.6Product weight5.5 ksProduct length5.5 ksProduct length9.6Product length<	Power Source	Petrol
Figine ModelGCVxe 145 OHV AutochokeEngine ModelGCVxe 145 OHV AutochokeNet power output275 KW @2900 rpmStarterRecoilStarter0.95 LFuel Tank Capacity0.4 LCutting width6 GraCutting MethodStellCutting MethodStellCutting height adjustmentGolistinaCutting height positionsSolisionsCutting height positionsSol-PoreliedTartionRear-Oller driveMaximum speed forward4.1 km/hCollector typeHydri with full indicatorVierational scalar discussionSol-Sol-Sol-Sol-Sol-Sol-Sol-Sol-Sol-Sol-	Capacity	145 cc
Net power output2.75 kW @2900 rpmStarterRecoilFuel Tank Capacity0.95 LFugine oil tank capacity0.4 LCutting width46 cmCutting MethodCollectingDeck materialSteelCutting height adjustment0.9 rollinisCutting height positions5 positionsCutting height positions0.9 rollinisCutting height ange0.9 rollinisCutting height ange8elf-propelledTactionRear-roller driveMaximum speed forward4.1 km/hCollector tapacity55 LCollector tapacity180 nm /ROLLER grooved wheels on ball bearingsGildA9.6Masinum speed forward4.8Ausinum speed forward9.6Starter desound power level (LWA)9.6Prater desound pressure level at perator er dR(A)9.6Pack weight9.6 scal scal scal scal scal scal scal scal	Engine Brand	Honda
StarterRecoilFuel Tank Capacity0.95 LEngine oil tank capacity0.4 LCutting width46 cmCutting MethodCollectingDeck materialSteelCutting height adjustment5 positionsCutting height positions5 positionsCutting height ange0.0 70 mmTractionRear-roller driveMaximum speed forward4 Ikm/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGaranteed sound power level (LWAP)9Pack arding negative and and sound power level at the sound provem level at the	Engine Model	GCVxe 145 OHV Autochoke
Fue Tank Capacity0.95 LFugine oil tank capacity0.4 LCutting width46 cmCutting MethodCollectingDeck materialSteelCutting height adjustmentGentralisedCutting height positions5 positionsCutting height nange02 -70 mmDrivingSelf-propelledTractionRear-roller driveMaximum speed forward51 LCollector capacity55 LCollector tapacity63 CGuaranteed sound power level (LWA)96Fubraced sound power level add(A)96Pack meingen (LWXH)96Pack weight37.4 kgProduct weight35.9 x 460Product useght35.9 x 460Product useg	Net power output	2.75 kW @2900 rpm
Engine oil tank capacity0.4 LEngine oil tank capacity0.4 LCutting width46 cmCutting MethodCollectingDeck materialSelelCutting height adjustment0.4 DCutting height positions0.7 O mmCutting height range0.7 O mmTrationSelf-propelledMaximum speed forward4.1 km/hCollector capacity5 LCollector type1.8 Ord mr. ROLLER grooved wheels on ball bearingsMethod9.6 Carcelled additionationCollector space level (LWA)- granteed sound power level (LWA)- gerared regionation9.6 Carcelled additionationMethod9.6 Carcelled additionationMethod9.6 Carcelled additionationProduct weight9.6 Carcelled additionationProduct weight9.6 Carcelled additionationProduct length9.6 Carcelled additionationProduct weight9.6 Carcelled additionationProduct weight	Starter	Recoil
Cutting width46 cmCutting MethodCollectingDeck materialSteelCutting height adjustmentCentralisedCutting height positions20 - 70 mmCutting height range20 - 70 mmCutting height rangeSeel-DrivingSelf-propelledTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LWA) - B(A)96Vibration level hand (m/s2)9.6Reasured sound pressure level at (A)9.6Pack weight9.45 x 530 x 460Pack weight159 numProduct length159 numProduct length159 numProduct weight159 num	Fuel Tank Capacity	0.95 L
Cutting MethodCollectingDeck materialStelCutting height adjustmentContralisedCutting height positions5 positionsCutting height range20 - 70 mmCutting height rangeSelf-propelledTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuranteed sound power level (LWA)9Kibration level hand (m/s2)4.8Masumed sound pressure level at (Masimed sound	Engine oil tank capacity	0.4 L
Deck materialSteelDeck materialCentralisedCutting height adjustmentSpositionsCutting height positionsSpositionsCutting height rangeSolf-propelledDrivingSelf-propelledTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacitySpi LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LwA) - B(B(A)96Vibration level hand (m/s2)4.8Measured sound power level at (Spi Spi Spi Spi Spi Spi Spi Spi Spi Spi	Cutting width	46 cm
Cutting height adjustmentCentralisedCutting height positions5 positionsCutting height range20 - 70 mmDrivingSelf-propelledTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LwA) - B(B(A)9Vibration level hand (m/s2)4.8Measured sound power level at (MAR)9Advinger and B(A)945 x 530 x 460Pack dimensions (LxWXH)3.5 kgProduct weight1590 mmProduct useight1590 mmProduct useight1590 mmProduct weight1590 mmProduct Weight150 mmProduct Weight150 mm	Cutting Method	Collecting
Cutting height positions5 positionsCutting height range20 - 70 mmDrivingSelf-propelledTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LWA) - (B(A)96Vibration level hand (m/s2)4.8Masured sound power level dB(A)96Pack dimensions (LxWxH)96Pack weight35 kgProduct weight35 kgProduct length36 kgProduct length1500 mmProduct weight500 mm	Deck material	Steel
Cutting height range20 - 70 mmDrivingSelf-propelledTractionRear-roller driveMaxinum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LuwA) - B(B(A)9Vibration level hand (m/s2)4.8Masured sound power level dB(A)9Pack dimensions (LxWxH)9Pack dimensions (LxWxH)945 x 530 x 460Product weight37.4 kgProduct length190 mmProduct length190 mmProduct weight510 mm	Cutting height adjustment	Centralised
PrivingSelf-propelledTractionRear-roller driveMaximum speed forward4.1 km/hCollector capacity55 LCollector rypeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LwA) - dB(A)9Vibration level hand (m/s2)4.8Measured sound pressure level at operator ear dB(A)96Pack dimensions (LxWxH)945 × 530 × 460Product weight37.4 kgProduct length190 mmProduct length190 mm	Cutting height positions	5 positions
TractionRear-roller driveMaximum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LwA) - a (B(A))96Vibration level hand (m/s2)4.8Measured sound power level dB(A)96Pack dimensions (LxWXH)96Pack dimensions (LxWXH)915 x 530 x 460Product weight37.4 kgProduct weight1590 mmProduct weight1500 mm	Cutting height range	20 - 70 mm
Maximum speed forward4.1 km/hCollector capacity55 LCollector typeHybrid with full indicatorWheels180 mm/ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LwA) - dB(A)9Vibration level hand (m/s2)4.8Measured sound power level dB(A)9Measured sound pressure level at operator ear dB(A)96Pack dimensions (LxWXH)96Pack weight37.4 kgProduct weight1590 mmProduct length510 mm	Driving	Self-propelled
Collector capacity55 LCollector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LuwA) - dB(A)96Vibration level hand (m/s2)4.8Measured sound power level dB(A)96Measured sound power level dB(A)96Pack dimensions (LxWxH)96Pack weight915 x 530 x 460Product weight35 kgProduct weight1500 mmProduct weight510 mm	Traction	Rear-roller drive
Collector typeHybrid with full indicatorWheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LwA) - dB(A)96Vibration level hand (m/s2)4.8Measured sound power level dB(A)96Measured sound power level dB(A)96Pack dimensions (LxWxH)945 × 530 × 460Pack weight37.4 kgProduct weight1590 mmProduct weight510 mm	Maximum speed forward	4.1 km/h
Wheels180 mm /ROLLER grooved wheels on ball bearingsGuaranteed sound power level (LuwA)96Vibration level hand (m/s2)96Measured sound power level dB(A)96Measured sound power level dB(A)96Pack dimensions (LxWxH)945 × 530 × 460Pack weight37.4 kgProduct weight1590 mmProduct length500 mmProduct weight510 mm	Collector capacity	55 L
Guaranteed sound power level (LwA) -96Vibration level hand (m/s2)4.8Measured sound power level dB(A)96Measured sound pressure level at operator ear dB(A)a0aPack dimensions (LxWxH)945 x 530 x 460Pack weight37.4 kgProduct weight1590 mmProduct weight510 mm	Collector type	Hybrid with full indicator
dB(A)96Vibration level hand (m/s2)4.8Measured sound power level dB(A)96Measured sound pressure level at operator ear dB(A)96Pack dimensions (LxWxH)96Pack weight37.4 kgProduct weight1590 mmProduct width510 mm	Wheels	180 mm /ROLLER grooved wheels on ball bearings
Measured sound power level dB(A)96Measured sound pressure level at operator ear dB(A)80Pack dimensions (LxWxH)945 × 530 × 460Pack weight37.4 kgProduct weight35 kgProduct length1590 mmProduct width510 mm		96
Measured sound pressure level at operator ear dB(A)80Pack dimensions (LxWxH)945 x 530 x 460Pack weight37.4 kgProduct weight35 kgProduct length1590 mmProduct width510 mm	Vibration level hand (m/s2)	4.8
operator ear dB(Å)80Pack dimensions (LxWxH)945 x 530 x 460Pack weight37.4 kgProduct weight35 kgProduct length1590 mmProduct width510 mm	Measured sound power level dB(A)	96
Pack weight 37.4 kg   Product weight 35 kg   Product length 1590 mm   Product width 510 mm	-	80
Product weight 35 kg   Product length 1590 mm   Product width 510 mm	Pack dimensions (LxWxH)	945 x 530 x 460
Product length 1590 mm   Product width 510 mm	Pack weight	37.4 kg
Product width 510 mm	Product weight	35 kg
	Product length	1590 mm
Product height 1090 mm	Product width	510 mm
	Product height	1090 mm



RRP: £579.00 Promo: £499.00 Warranty: 5\* year extended warranty (T&Cs apply)